



ITEM	NAME OF PART	MATERIAL	NOTES
2	Pin header	Copper	Sn Plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/15	/	300/10
VDE 标准/VDE Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	II/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	320/20	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	4	/
爬电/Pitch(mm)/绝缘范围/Poles	5.08/N=02~24P		
使用温度范围/Operating Temperature(°C)	-40°C~+105°C		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: SURFACE:

MAT NO.:

STATUS:

APPD:

CHKD:

DRT:

® 宁波三安电子科技有限公司  
Sanan Electrical Technology Co. Ltd

NAME: ZESARC-5.08-XXP-1Y-100A(H)

DRAWING NO.:

SCALE:

TYPE:

SIZE: A4  
mm  
inch

REV

1/1

公差/General	tolerances(mm)
0	>3
2	>6
3	>10
6	>18
10	>30
18	>50
30	>80
50	>120
80	>180
120	>250
180	>315
250	>400
315	>500
400	>500
500	>500
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±0.80	±1.05
±1.15	±1.60
±2.20	±2.50

0.1/10  
±Z