



Total Pitch Tolerances		Nominal dimension range																																															
In mm		In mm																																															
0	over	0	over	30	over	53	over	70	over	90	over	115	over	150	over	250	over	350	over	500	over	30	over	53	over	70	over	90	over	115	over	150	over	200	over	250	over	320	over	10	over	10	over	100	over	100	over	150	over
±0.18E-02	to	±0.20E-02	to	±0.3E-02	to	±0.35E-02	to	±0.44E-02	to	±0.50E-02	to	±0.60E-02	to	±0.70E-02	to	±0.85E-02	to	±0.20E-02	to	±0.25E-02	to	±0.30E-02	to	±0.35E-02	to	±0.44E-02	to	±0.55E-02	to	±0.70E-02	to	±0.80E-02	to	±0.90	to	±0.2	to	±0.3	to	±0.3	to	±0.2	to	±0.3	to	±0.5	to		

UL 标准 /UL Standard:	B	C	D
额定电压/电流 /Rated Voltage(V)/Current(A)	300/10	/	300/10
IEC 标准 /IEC Standard:	III/3	III/2	II/2
过压类别 /Overvoltage Category /污染等级 /Pollution Degree	III/3	III/2	II/2
额定电压/电流 /Rated Voltage(V)/Current(A)	250/10	320/10	400/10
额定脉冲电压 (KV) /Rate Impulse Voltage (KV)	4	4	4
使用温度范围 /Operating temperature (°C)	-40~+105		
符合RoHS环保要求 /Conform to RoHS	Yes		

ITEM	NAME OF PART	Q'TY	MATERIAL
DWG.	MYZ	DATE	22.10.12
CHK.	DATE	SCALE	1:1
APP.	DATE	NAME	2EKELF-5.0-04P
DWGNO.		XXXXX	

REV	CONTENT	CHK	DATE
V0.0	CONTENT	MYZ	22.10.12


宁波三安电子科技有限公司
 Sanan Electrical Technology Co., Ltd.